

Specifications

MODEL	TG2661	TG3061	TG3073
Engine			
Power Unit	Kawasaki FX730	Kohler Command Pro	Kohler Command Pro
Horsepower	26 HP (19.4 KW)	30 HP (22.4 KW)	30 HP (22.4 KW)
Displacement	726 cc	747 cc	747 cc
Crankshaft Orientation	Vertical	Vertical	Vertical
Crank Case Capacity	2.25 qt. (2.1 L)	2 qt. (1.9 L)	2 qt. (1.9 L)
Cooling	Air	Air	Air
Air Cleaner	Canister Type	Canister Type	Canister Type
Fuel System			
Fuel Type	Gas	Gas	Gas
Fuel Location	Dual Tanks	Dual Tanks	Dual Tanks
Fuel Tank Capacity	8 US gal (30.3 L)	12 US gal (45.4 L)	12 US gal (45.4 L)
Fuel Cap	Vented w/Tether	Vented w/Tether	Vented w/Tether
Drive Train			
Transmission	Dual Transaxles ZT-3400	Dual Pump & Wheel motors	Dual Pump & Wheel motors
Steering	Dual Control Levers	Dual Control Levers	Dual Control Levers
Hydraulic Capacity	1 US gal (3.8 L)	1 US gal (3.8 L)	1 US gal (3.8 L)
Filter	Spin-on Replaceable	Spin-on Replaceable	Spin-on Replaceable
Travel Speed Forward	0-10 MPH (0-16 KPH)	0-14 MPH (0-22.5 KPH)	0-14 MPH (0-22.5 KPH)
Travel Speed Reverse	0-4 MPH (0-6.4 KPH)	0-4 MPH (0-6.4 KPH)	0-4 MPH (0-6.4 KPH)
Tires			
Drive Tires	Turf	Turf	Turf
Front Caster Wheels	13x5.0-6 4 ply	14x5.0-6 4 ply	14x5.0-6 4 ply
Brakes			
Park Brake	Disc Type	Disc Type	Disc Type
Park Brake Equipment	Hand Engaged	Hand Engaged	Hand Engaged
Electrical System			
Ignition	Electric Key Start	Electric Key Start	Electric Key Start
Tachometer/Hour Meter	Digital	Digital	Digital
Battery	12V - 230 CCA	12V - 230 CCA	12V - 230 CCA
Operator Presence Starting System	Standard	Standard	Standard

MODEL	TG2661	TG3061	TG3073
Operator Area			
Seat	Full Suspension w/Arm Rests	Full Suspension w/Arm Rests	Full Suspension w/Arm Rests
Seatbelt	Standard	Standard	Standard
ROPS	Fold Down	Fold Down	Fold Down
Beverage Holder	Molded-In	Molded-In	Molded-In
Storage Tray	Molded-In	Molded-In	Molded-In
Mower Decks			
Cut Width	61" (155 cm)	61" (155 cm)	73" (185.4 cm)
Deck Lift	Manual - Foot Lift	Manual - Foot Lift Optional - Electric	Power-Electric
Deck Thickness	10 Gauge	7 Gauge	7 Gauge
Cut Range	1½ to 5" (3.82 to 12.7 cm)	1½ to 5" (3.82 to 12.7 cm)	1½ to 5" (3.82 to 12.7 cm)
Increments	¼" Increments	¼" Increments	¼" Increments
Anti-Scalping Roller	Standard	Standard	Standard
Blade Drive	Single Belt	Single Belt	Single Belt
Blades	Fusion Hi-Lift	Fusion Hi-Lift	Fusion Hi-Lift
Blade Tip Speed	17,500 FPM	18,500 FPM	18,500 FPM
Dimensions			
Transport Width	66" (167.6 cm)	66" (167.6 cm)	78" (198.1 cm)
Transport Length	86" (218.4 cm)	88" (223.5 cm)	88" (223.5 cm)
Height with ROPS Up	73" (185.4 cm)	74" (187.9 cm)	74" (187.9 cm)
Ground Clearance	4" (10.2 cm)	5¼" (13.3 cm)	5¼" (13.3 cm)
Weight	1,400 lbs. (635 kg)	1,400 lbs. (635 kg)	1,550 lbs. (703 kg)
Options			
Operator Comfort	Sun Shape	Canopy	Canopy
Work Light	Halogen	Halogen	Halogen
Tires	Bar Type	Bar Type	Bar Type
Warranty			
Warranty	3 Year Limited Warranty, Lifetime Limited Deck Weldment Warranty**	3 Year Limited Warranty, Lifetime Limited Deck Weldment Warranty**	3 Year Limited Warranty, Lifetime Limited Deck Weldment Warranty**

**3 year limited warranty (third year parts only) includes drive train, electromagnetic clutch, deck and cutter spindles. See Dealer for complete details. Engine warranty administered through engine manufacturer.

Since 1968, Tiger has engineered and manufactured Tiger products that meet all ASTM safety guidelines. Contact your dealer and ask about purchasing a Tiger mower and or Tiger OEM parts. Our parts last longer, are more durable and fit the Tiger mowers.



Tiger Corporation
3301 North Louise Ave.
Sioux Falls, South Dakota 57107
800-843-6849
www.tigermowers.com

Dealer Info:



TIGER ZTR MOWERS

Provide superior performance and handling at speeds up to 14 mph. Receive a groomed appearance in difficult terrain and around landscaping or curbs & gutters with a Tiger ZTR mower. All models come standard with fully floating decks and anti-scalping rollers. Tough grease able cast spindle assemblies provide support for the Tiger Fusion blades. All models of ZTR's carry a three year Commercial Limited warranty and Lifetime warranty on the deck weldment.

QUICK FOOT™ DECK RELEASE



CUTTING HEIGHT ADJUSTMENT FROM 1 1/2" TO 5" WIDTH

10-gauge deck with welded 3/8" rolled edges



DUAL HYDRO-GEAR ZT-3400 DRIVE SYSTEMS



7" COOLING FANS PROVIDE SPEED AND PERFORMANCE FOR ALL DAY CUTTING.

Mold-In operator storage and beverage holders

TG 2661™

OPERATOR CONSOLE



FEATURES:
DIGITAL TACHOMETER
HOUR METER
THROTTLE
CHOKE
LOW OIL SENSOR
KEYED IGNITION
MOWER PTO SWITCH
OPTIONAL LIGHT SWITCH (SHOWN)

Fold Down ROPS

Halogen work lights - optional



Common Features

FUSION® BLADES



STAY SHARP LONGER WITH HIGH LIFT, HEAT TREATED STEEL BLADES

5" DISCHARGE CHUTE



FLEXIBLE GUARD PROVIDES EASY TRIMMING AROUND LANDSCAPE

FULL SUSPENSION SEAT



DUAL ARM RESTS, LUMBAR WITH TILT, FORE/AFT ADJUSTMENT STANDARD

FILTER SYSTEM



MAXIMIZE YOUR ENGINE PERFORMANCE WITH EASY ACCESS TO AIR FILTER

OPERATOR CONSOLE



FEATURES:
DIGITAL TACHOMETER
HOUR METER
THROTTLE, CHOKE
LOW OIL SENSOR
TEMPERATURE SENSOR
KEYED IGNITION
POWER DECK LIFT
MOWER PTO SWITCH
OPTIONAL LIGHT SWITCH (SHOWN)

POWER DECK LIFT



ADJUST CUT HEIGHT ON THE GO IN 1/4" INCREMENTS

Fold Down ROPS with Optional Canopy

Pivoting Front Axle with fully floating suspended deck allows the operator to make tight contouring cuts around landscape. Deck height can be locked when cutting on uneven ground.

DUAL PUMP AND WHEEL MOTORS



DUAL VARIABLE DISPLACEMENT PUMPS WITH HIGH EFFICIENCY MOTORS AND COOLING FANS DELIVERS SUPERIOR RESPONSE AND CUTTING SPEED

7-gauge deck with welded 3/8" rolled edges



TG 3073™



TG 3061™

Dual Fuel Tanks

Halogen work lights - optional